



### Features:

- Horizontal or Vertical Installation
- Applied over solid substrate with proper underlayment

### Panel Lengths

Available up to 40'

### Panel Width

36" Coverage

### Panel Depth

1.25"

### Gauges

24, 26 optional - Steel  
0.032 - Aluminum

### Finish Options:

ProFinish 500 (PVDF) Colors & Acrylic Coated Galvalume®

Allowable Live Load in PSF			Span In Feet (steel only)					
SPAN TYPE	GAUGE	KSI	3'	4'	5'	6'	7'	8'
SINGLE SPAN	22	50	165	93	54	35	24	18
DOUBLE SPAN	22	50	166	94	60	42	31	24
THREE OR MORE SPANS	22	50	205	116	75	52	38	27
SINGLE SPAN	24	50	119	67	40	26	18	10
DOUBLE SPAN	24	50	121	70	45	31	23	18
THREE OR MORE SPANS	24	50	157	90	58	40	29	20
SINGLE SPAN	26	80	111	60	35	23	16	11
DOUBLE SPAN	26	80	143	80	47	30	21	16
THREE OR MORE SPANS	26	80	155	89	57	35	24	20

Test	Water Spray Leakage Test	Static Water Leakage Test
	5 GAL/SF/HR for 15 Mins.	6" Water depth for 7 days
<b>PBR Panel</b>	No signs of water leakage during the test period and 15 minutes after.	Passed - No Leakage