



*OPTIONAL ADJUSTABLE REVEAL
0" TO 3" IN 1/2" INCREMENTS
[0mm TO 76.2mm IN 12.7mm INCREMENTS]

Features:

- Horizontal or Vertical Installation
- Wall and Soffit Application
- Applied over solid substrate with proper underlayment.
- Stiffening Ribs, Striations and Pencil Ribs available
- Venting for airflow- single, double or triple looped venting
- Adjustable reveal available 0-3" in 1/2" increments

Finish Options:

ProFinish 500 (PVDF) Colors & Acrylic Coated Galvalume®, Woodgrain & Specialty finishes upon request

Panel Lengths:

Minimum panel length - 2'-0"
Maximum panel length - 40'-0"
Field forming available for panels over 40'-0"

Panel Depth:

1 1/2"

Panel Coverage:

19" nominal
Special widths available upon request

Material Options:

Steel, Aluminum, Copper, and Zinc

Gauge Options:

24 gauge standard, 22 gauge optional - Steel
0.032 and 0.040 - Aluminum
16 oz and 20 oz - Copper
0.8 mm and 1.0 mm - Zinc

Clarifications:

RMP recommends all panels to be striated to minimize "oil canning".

Purchaser must specify smooth or striated panel on order.

RollFab uses top quality materials specifically designed for rollforming applications, which are tension leveled to help minimize oil canning.

Oil canning is naturally inherent in sheet metal and is not a cause for rejection.