



Features:

- Roof or Wall Application
- Horizontal or Vertical Installation
- Applied over solid substrate or open framing
- 2 piece concealed clip designed for thermal movement
- Can be curved to a minimum radius of 196"
- Field applied sealant - ensures weather tightness

Panel Lengths:

- Minimum 5' up to 50'
- Field forming available for panels over 50'
- 2" Rib Height, 18" coverage standard (12.5" and 16" special order)

Panel Depth:

- 2" seam depth, (system depth is 2.5" with clip)

Product Options:


- Finishes: Kynar 500 (PVFD) Colors and Acrylic Coated Galvalume
- Available Gauges: 24 ga Standard; 22 ga Optional
- Also available in 20 oz Copper, 0.040 Aluminum, 0.8mm Zinc
- Mechanically seamed integral side lap seam
- Single or double lock; UL rated in either seam type
- Striated surface standard
- Oil Canning is NOT a cause for rejection
- Weathertight warranty may be available, inquire for details

Curving Data:


- Convex Radius - 10' (3048mm) Minimum
- Concave Radius - N/A
- Field forming available if req'd

Testing:

- UL-263 Fire Resistance Rating
- UL-790 Class A Fire Resistance
- UL-2218 Class 4 Impact Resistant
- CEGS 07416 US Army Corp of Engineers Rated, ASTM E1592
- UL-580 Class 90 Wind Uplift Construction No. 90, 176, 180, 238, 238A, 238B, 238C, 437, 449, 451, 452, 487, 506, 506A, 506B, 576, 577, 583
- Miami Dade County ASTM-1897 approved: FM I 90 protocol
- ASTM 2140 Submersion Test approved PA-125(FM4471)
- ASTM E-E1646-95 Water Infiltration
- ASTM E-E1680-95 Air Filtration



OPTION MS200HPC @ 90°



MS200HPC PANEL CLIP

Clarifications:

- All panels will be supplied with striations unless specified otherwise, in writing by purchaser.
- Rollfab utilizes top quality materials specifically designed for rollforming applications, which are tension leveled to help minimize oil canning. Oil canning is naturally inherent in sheet metal and is not grounds for rejection.
- Kynar 500 is a registered trademark of Elf Atochem North America Inc.
- Galvalume is a registered trademark of BEIC International, Inc.

