USES:

Soffits, Cladding, Privacy, Enclosure Screens, Ceilings, Walls, Battens, Decorative Elements, Signage, Vertical or Horizontal Installations





Mosaic works beautifully on exteriors as well as interiors and has a wide variety of profiles for use for cladding, soffits, enclosure screens, ceilings, walls, partitions, and a variety of custom solutions. The design capabilities are endless with the versatility of Mosaic. The product is lightweight, durable and our licensed proprietary sublimation process will make its low maintenance beauty last for years.

WOOD FINISHES







- Lightweight & Durable
- Time & Labor Savings with Ease of Installation
- 100% Recyclable

SMOOTH ONLY

10 % - 20 % GLOSS

- Architectural Soffit & Wall Applications
- Installed Over Open Framing or Solid Substrate
- Battens Mechanically Attached with Internal Fastenina

SMOOTH ONLY

25 % - 35 % GLOSS

- 15 Year Wood Grain Finish Warranty, 20 Year Solid Colors
- Specialty Warranties Available by Request
- Perfect for Exterior or Interior Applications
- Matching End Caps in Solid Colors or Wood Grain Finishes (Battens)
- Paint Finish Testing: AAMA 2605 & Class "A" Fire Rating
- Custom Colors & Color Matchina Available
- Ask us about our other product lines

V-RATING

- V1 MINIMAL VARIANCE
- V2- COLOR OR PATTERN VARIANCE
- V3- COLOR AND PATTERN VARIANCE



SMOOTH ONLY

25%-35% GLOSS



SMOOTH ONLY

20%-35% GLOSS





SELECTIONS PLEASE REQUEST COLOR SAMPLES.

DIMENSIONS:

PLANKS (12' OR 24' LENGTHS)

SMOOTH ONLY

10 % - 20 % GLDSS

2.5" V-GROOVE 4" V-GROOVE

6" V-GROOVE 8" V-GROOVE

10" V-GROOVE 6" FLUSH PLANK

SOLID BATTENS (24' LENGTHS)

1"×3" 2"x8" (2 or 6 screw

1"×4" 1"×5"

1"×6"

SMOOTH ONLY

2%-6% GLDSS

1"x8"

FOR ACCURATE COLOR

BATTEN ASSEMBLIES (24' LENGTHS)

FINE TEXTURE ONLY

3 % - 7 % GLDSS

2"×2" 2"×3"

SMOOTH ONLY

10%-20% GL0SS

2"×4"

Some batten assemblies are available in various

2"×6" configurations

2"×8"

2"×10'

2"×12'

4"×2" 6"×1"

1"x3" L-Connect 1"x6" L-Connect 1"x4" L-Connect 4"x8" L Connect

1"x5" L-Connect

SMOOTH ONLY

10 % -16 % GLOSS

SMOOTH ONLY

20%-30% GL0SS