Product Information

- The perfect architectural solution for a variety of exterior and interior applications including sunshades, privacy screens, fencing, and decorative elements.
- Made of 6063-T6 extruded aluminum alloy.
- Both prepunched and t-shaped end caps available.
- Lightweight, durable and our licensed proprietary sublimation process makes its beauty last for years.

Available Finishes

Solid colors, woodgrains, and specialty finishes.

Visit lumabuilt.com to view all available finishes.

Warranty

Woodgrains: 15-year standard warranty (20 year

specialty warranties on request)

Solid Colors: 20-year standard warranty

Full details are available at lumabuilt.com.

Testing Information

- System Testing with CA & PA Stamps: ASTM E2768/E84, ASTM E136, AAMA 1402
- Paint Finish Testing: AAMA 2605
- Fully ICC Certified: ESR-5449
- · Class "A" Fire Rating
- FL Supplement with HVHZ (ESR-5449)

SOLID BATTENS		
PROFILE/PRODUCT	LENGTH	WEIGHT
1" x 3" Solid Batten	24'*	.716 lb/ft
1" x 4" Solid Batten	24'*	.869 lb/ft
1" x 5" Solid Batten	24'*	1.025 lb/ft
1" x 6" Solid Batten	24'*	1.180 lb/ft
1" x 8" Solid Batten	24'*	1.947 lb/ft
2" x 8" Solid Batten	24'*	2.183 lb/ft
2" x 8" 6-Screw Boss Solid Batten	24'*	2.934 lb/ft
4" x 10.75" Cee Fin	24'*	4.898 lb/ft

L-CONNECT ASSEMBLIES

PROFILE/PRODUCT	LENGTH	WEIGHT
1" x 3" L-Connect Batten	24'*	1.013 lb/ft
1" x 4" L-Connect Batten	24'*	1.205 lb/ft
1" x 5" L-Connect Batten	24'*	1.396 lb/ft
1" x 6" L-Connect Batten	24'*	1.586 lb/ft
4" x 8" L-Connect Batten	24'*	3.156 lb/ft

Custom lengths are available upon request. Order minimums may apply

BATTEN ASSEMBLIES

PROFILE/PRODUCT	LENGTH	WEIGHT
2" Batten Base	24'*	.535 lb/ft
2" Batten Cap	24'*	.558 lb/ft
3" Batten Cap	24'*	.804 lb/ft
4" Batten Cap	24'*	.996 lb/ft
6" Batten Cap	24'*	1.525 lb/ft
8" Batten Cap	24'*	2.408 lb/ft
Batten Extension	24'*	.849 lb/ft
6" x 1" Batten Assembly	24'*	1.597 lb/ft
4" x 2" Batten Assembly	24'*	1.500 lb/ft

EXPOSED BRACKETS


PROFILE/PRODUCT	LENGTH	WEIGHT	THICKNESS
1" U Bracket	3"-12"	.111 lb/ft	.125"
2"UBracket	3"-12"	.221 lb/ft	.125"
LBracket	3"-12"	.110 lb/ft	.125"
Angle Bracket	3"-12"	.115 lb/ft	.125"








SOLID BATTENS







4" X 10.75" CEE FIN





























The L-Connect Assembly provides exceptional flexibility and design versatility within the Mosaic Batten System. Its unique profile allows fasteners to be installed through either side of the batten, concealing them completely once assembled for a clean, uninterrupted appearance. This design enables secure attachment while preserving a refined, seamless look-ideal for architectural applications where visual continuity and precision detailing are essential. The L-Connect Assembly gives designers the freedom to achieve complex layouts without compromising aesthetics or installation efficiency.

L-CONNECT ASSEMBLIES





1" X 6" L-CONNECT ASSEMBLY













EXPOSED BRACKETS









TEND CAPS



T End Caps feature a quick, press-fit design that delivers a seamless, wood beam-like finish at the end of each batten. For long-term hold and stability, a small amount of silicone adhesive is recommended during installation.

FLAT END CAPS



Flat End Caps feature a flat design with pre-punched holes for customer-supplied fasteners, allowing for quick and secure installation. Once attached, the exposed rivets provide a clean, industrial appearance that complements a wide range of architectural styles.

